MITSUBISHI MOTORS **GENUINE PARTS**

OUTLANDER TAILGATE PROTECTOR MZ574481EX INSTALLATION AND HANDLING INSTRUCTIONS



Thank you for purchasing the Mitsubishi Genuine Accessory.

To install and use the product correctly with proper knowledge of it, read this publication carefully. Keep this publication for reference when maintenance is required.

Attention

This publication gives precautionary instructions in the boxes titled as follows. Read through these instructions thoroughly.



Caution

Describes precautions that should be observed in order to prevent injury or damage to the vehicle or its components, which may occur if sufficient care is not taken.



Note

Provides additional information that facilitates installation work.

- Failure to follow these instructions not only prevents the product from working properly but may lead to trouble with the vehicle. Be sure to follow all instructions carefully.
- If there is anything unclear about the installation, handling and/or usage of the product, contact your Mitsubishi Motors dealer for clarification.
- Mitsubishi Motors Corporation is not responsible for any defects or difficulties caused by or resulting from the failure to follow given instructions.
- We recommend you to have the installation performed at an authorized Mitsubishi Motors dealer.

To the dealer:

Be sure that the customer receives this publication.

TOOLS (Make the following tools ready for use.)

Isopropyl alcohol or degreaser

Neutral detergent

Spray bottle

Squeegee

Soft cloth














■ COMPONENTS (Make sure that all of the following components were included in the kit.)




PRECAUTIONS


When the ambient temperature is lower than 20°C, heat the protector and its application surface on the tailgate (to $20 - 38^{\circ}$ C).

INSTALLATION PROCEDURES

A. ATTACHING THE TAILGATE PROTECTOR



<Sectional view>





- 1) Wipe clean the protector attaching surface of the tailgate with isopropyl alcohol or degreaser, then dry the surface completely. Oil or dirt remaining on the attaching surface can be the cause of trapped air bubbles or peeling off of protector.
- 2) Remove the backing strip from the Tailgate Protector (1).
- Spray 0.5 1% neutral detergent solution over the tailgate where the protector will be attached and over the adhesive side of the protector.
- Position the protector on the tailgate at the bottom end of the tailgate, aligning its right and left ends with the press lines on the tailgate.



Note

The right and left ends of the protector should be evenly spaced against the tailgate edges.

- 5) Press the protector against the tailgate using a squeegee wrapped with a soft cloth. Starting from either left or right end, move the squeegee vertically to squeeze out the solution and air bubbles.
- 6) Peel off the application tape by slowly pulling it parallel with the protector.
- 7) After peeling off the application tape, check that the protector is firmly applied to the tailgate. If any floating portion is found, press the portion with squeegee.

